



AG FORKS

AF60 | AF66
AF72 | AF78



WORKSITE PRO

COMMERCIAL WORKSITE PRODUCTS

SPECIFICATIONS

AF60 / AF66 / AF72 / AF78

- Tines easily penetrate pen-packed material for quicker clean-out. Visibility to the tines is unrestricted.
- Bolt-on tines are easy to replace. Come equipped with standard 10.5-inch tine spacing.
- Like all Worksite Pro™ attachments, these ag forks are optimized to work with John Deere 300-Series Skid Steers and Compact Track Loaders, and are compatible with most competitive models. See your local John Deere skid steer dealer for details.

	AF60	AF66	AF72	AF78
Number of Tines	6	7	7	8
Weight	370 lb. (168 kg)	395 lb. (179 kg)	435 lb. (197 kg)	445 lb. (202 kg)
Height	22 in. (561 mm)	22 in. (561 mm)	22 in. (561 mm)	22 in. (561 mm)
Length	34 in. (864 mm)	34 in. (864 mm)	34 in. (864 mm)	34 in. (864 mm)
Width	59 in. (1500 mm)	65 in. (1652 mm)	71 in. (1804 mm)	77 in. (1956 mm)
Tine Spacing	10.5 in. (267 mm)	10.5 in. (267 mm)	10.5 in. (267 mm)	10.5 in. (267 mm)
Usable Length	25.3 in. (642 mm)	25.3 in. (642 mm)	25.3 in. (642 mm)	25.3 in. (642 mm)
Vehicle Compatibility	313 and 315	313, 315, 317, and 320	317, 320, 325, 328, and CT322	317, 320, 325, 328, and CT322

WORKSITE PRO™



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

