

Brush-Tined Grapples

GT72 | GT80



JOHN DEERE



Brush-Tined Grapples

GT72 | GT80



Specifications

- Each unit includes two independent-action grapples that allow different-sized objects to be grasped and retained.
- Grapple opening of 971 mm (38.2 in.) allows large payloads.
- 100-mm (4 in.) tine spacing works well for sorting or sifting materials.
- Like all Worksite Pro™ attachments, these grapples are optimized to work with John Deere D- and E-Series Skid Steers and Compact Track Loaders, and 244J Loader, and are compatible with most competitive models. See your local John Deere skid steer dealer for details.

	GT72	GT80
Width	1816 mm (71.5 in.)	2043 mm (80.4 in.)
Length	990 mm (39.0 in.)	990 mm (39.0 in.)
Height		
Grapple Closed	725 mm (28.5 in.)	725 mm (28.5 in.)
Grapple Open	1167 mm (45.9 in.)	1167 mm (45.9 in.)
Grapple Opening	971 mm (38.2 in.)	971 mm (38.2 in.)
Number of Tines	16	18
Tine Spacing (opening between tines)	100 mm (4 in.)	100 mm (4 in.)
Operating Weight	434 kg (955 lb.)	465 kg (1,023 lb.)
Vehicle Compatibility	315, 318D/E, 320D/E, 326D/E, and 328D/E Skid Steers; CT315, 319D/E, and 323D/E Compact Track Loaders; and 244J Compact Loader	320D/E, 326D/E, 328D/E, and 332D/E Skid Steers; 319D/E, 323D/E, 329D/E, and 333D/E Compact Track Loaders; and 244J Compact Loader

WORKSITE PRO™

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

