



# POWER RAKES

PR60 | PR72B  
PR84B | PR96B



**WORKSITE PRO™**

COMMERCIAL WORKSITE PRODUCTS

SPECIFICATIONS

PR60 / PR72B / PR84B / PR96B

- Worksite Pro™ power rakes are perfect for landscape tasks such as seedbed preparation, rock raking, site development, and more.
- Adjustable end plates allow the power rake to do double duty as a box scraper, trapping and gathering stones for piling and pick-up.
- Long-life carbide teeth on roller dig, lift, and pulverize dirt.
- Heavy-duty drive chain is housed in a sealed oil bath to reduce maintenance.
- Power rake roller assemblies can rotate 20 degrees from center in either direction, allowing material to be moved left or right. (Requires 12-volt kit.)
- The exclusive forward and backward raking capability of the power rakes halves the time required for seedbed preparation.
- Like all Worksite Pro™ attachments, the power rakes are optimized to work with John Deere 300-Series Skid Steers and Compact Track Loaders, and are compatible with most competitive models. See your local John Deere skid steer dealer for details.

	PR60	PR72B	PR84B	PR96B
<b>Minimum Hydraulic Flow</b> . . . . .	13 gpm (49 L/min.) . . . . .	13 gpm (49 L/min.) . . . . .	16 gpm (60 L/min.) . . . . .	16 gpm (60 L/min.) . . . . .
<b>Raking Width</b> . . . . .	62 in. (1575 mm) . . . . .	72 in. (1827 mm) . . . . .	84 in. (2134 mm) . . . . .	90 in. (2438 mm) . . . . .
<b>Operating Width</b> . . . . .	72 in. (1829 mm) . . . . .	81 in. (2056 mm) . . . . .	93 in. (2362 mm) . . . . .	100 in. (2540 mm) . . . . .
<b>Length</b> . . . . .	59 in. (1499 mm) . . . . .	64 in. (1625 mm) . . . . .	64 in. (1625 mm) . . . . .	76 in. (1930 mm) . . . . .
<b>Height</b> . . . . .	31 in. (787 mm) . . . . .	31 in. (787 mm) . . . . .	32 in. (812 mm) . . . . .	32 in. (812 mm) . . . . .
<b>Box End Plates</b> . . . . .	front or rear . . . . .	front or rear . . . . .	front or rear . . . . .	front or rear . . . . .
<b>Tooth Roller Diameter</b> . . . . .	9 in. (229 mm) . . . . .	9 in. (229 mm) . . . . .	9 in. (229 mm) . . . . .	9 in. (229 mm) . . . . .
<b>Weight</b> . . . . .	938 lb. (425 kg) . . . . .	925 lb. (419 kg) . . . . .	1,050 lb. (476 kg) . . . . .	1,320 lb. (598 kg) . . . . .
<b>Angle Control</b> (12-volt kit required) . . . . .	12-volt actuation, . . . . . 0–20-deg. rotation	12-volt actuation, . . . . . 0–20-deg. rotation	12-volt actuation, . . . . . 0–20-deg. rotation	12-volt actuation, . . . . . 0–20-deg. rotation
<b>Vehicle Compatibility</b> . . . . .	313 and 315 . . . . .	317, 320, 325, 328, . . . . . 332, CT322, and CT332	317, 320, 325, 328, . . . . . 332, CT322, and CT332	317, 320, 325, 328, . . . . . 332, CT322, and CT332

www.JohnDeere.com

**WORKSITE PRO™**



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

