Snow/Utility Blades BL6B | BL7B | BL8B | BL9B | BL10B





Snow/Utility Blades

BL6B | BL7B | BL8B | BL9B | BL10B



- Worksite Pro[™] snow/utility blades provide additional productivity in snow removal and light dirt work.
- Blade angles hydraulically 30 degrees, right or left. Adjustable skid shoes are standard.
- · Blade oscillates 5 degrees, right or left.
- Four trip springs help protect the vehicle from sudden impacts with obstacles when blading snow.
 Trip springs can be locked out for light grading and dirt work.
- Bolt-on replaceable 152-mm (6 in.) edge is 13-mm (0.5 in.) thick. Available rubber cutting edges prevent damage to decorative surfaces.
- Blade height is 711 mm (28 in.); an 203-mm (8 in.) full-length extension is available.
- Like all Worksite Pro attachments, these blades are optimized to work with John Deere D-Series Skid Steers, Compact Track Loaders, 244J Loader, and 110 Tractor Loader Backhoe. They're also compatible with many competitive models. See your local John Deere skid steer dealer for details.

	BL6B	BL7B	BL8B	BL9B	BL10B
Width	1829 mm (72 in.)	2134 mm (84 in.)	2438 mm (96 in.)	2743 mm (108 in.)	3048 mm (120 in.)
Angled Width	1575 mm (62 in.)	1829 mm (72 in.)	2108 mm (83 in.)	2362 mm (93 in.)	2591 mm (102 in.)
Height	711 mm (28 in.)	711 mm (28 in.)	711 mm (28 in.)	711 mm (28 in.)	711 mm (28 in.)
Weight	432 kg (954 lb.)	461 kg (1016 lb.)	489 kg (1078 lb.)	512 kg (1128 lb.)	540 kg (1190 lb.)
Vehicle Compatibility	313 and 315 Skid Steers	313, 315, 318D, 320D, 326D, 328D, and 332D Skid Steers; CT315, 319D, 323D, 329D, and 333D Compact Track Loaders; and 110 Tractor Loader Backhoe	318D, 320D, 326D, 328D, and 332D Skid Steers; 319D, 323D, 329D, and 333D Com- pact Track Loaders; and 110 Tractor Loader Backhoe	318D, 320D, 326D, 328D, and 332D Skid Steers; 319D, 323D, 329D, and 333D Com- pact Track Loaders; and 244J Compact Loader	326D, 328D, and 332D Skid Steers; 319D, 323D, 329D, and 333D Compact Track Loaders; and 244J Compact Loader



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.



DKASUBCWP Litho in U.S.A. (10-05) www.JohnDeere.com