

Ag Utility Grapples

GU60 | GU66 | GU72 | GU78



JOHN DEERE



Ag Utility Grapples

GU60 | GU66 | GU72 | GU78



Specifications

- One-piece grapples provide a firm grasp for efficient hay and manure handling.
- Standard 114-mm (4.5 in.) tine spacing works well for sorting or sifting materials. Simply add tines for 38-mm (1.5 in.) spacing.
- Greaseable pivot points, 25.4-mm (1 in.) hardened pins, and cylinder rods provide long-term strength and durability.
- Grapple opening of 914 mm (36 in.) accommodates large payloads.
- Like all Worksite Pro™ attachments, these grapples are optimized to work with John Deere skid steers, compact track loaders, and 244J Loader, and are compatible with most competitive models. See your local John Deere skid steer dealer for details.

	GU60	GU66	GU72	GU78
Width	1502 mm (59 in.)	1652 mm (65 in.)	1804 mm (71 in.)	1956 mm (77 in.)
Length	970 mm (38.2 in.)	970 mm (38.2 in.)	970 mm (38.2 in.)	970 mm (38.2 in.)
Height				
Grapple Closed	700 mm (27.6 in.)	700 mm (27.6 in.)	700 mm (27.6 in.)	700 mm (27.6 in.)
Grapple Open	1162 mm (45.7 in.)	1162 mm (45.7 in.)	1162 mm (45.7 in.)	1162 mm (45.7 in.)
Grapple Opening	914 mm (36 in.)	914 mm (36 in.)	914 mm (36 in.)	914 mm (36 in.)
Number of Tines				
Standard	10	11	12	13
Optional	19	21	23	25
Tine Spacing				
Opening Between Tines	114 mm (4.5 in.)	114 mm (4.5 in.)	114 mm (4.5 in.)	114 mm (4.5 in.)
Optional Spacing	38 mm (1.5 in.)	38 mm (1.5 in.)	38 mm (1.5 in.)	38 mm (1.5 in.)
Operating Weight	225 kg (496 lb.)	235 kg (517 lb.)	247 kg (543 lb.)	258 kg (568 lb.)
Vehicle Compatibility	313 and 315	313, 315, CT315, 318D/E, 319D/E, 320D/E, and 323D/E	318D/E, 319D/E, 320D/E, 323D/E, 326D/E, 328D/E, 329D/E, 332D/E, and 333D/E	318D/E, 319D/E, 320D/E, 323D/E, 326D/E, 328D/E, 329D/E, 332D/E, and 333D/E

WORKSITE PRO™

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

